

**2010**

## **ASEC INDUSTRIES PTE LTD**

No. 1 Upper Aljunied Link,  
#08-02, Joo Seng Warehouse Block A, Singapore 367901

TEL: (65) 6383 4368 / 6284 2051

FAX: (65) 6383 4369

Email: [shirleytan@asec.com.sg](mailto:shirleytan@asec.com.sg)

Website: [www.asec.com.sg](http://www.asec.com.sg)

**[TOOL CATALOGUE]**

Specification subject to change without prior notice

## Table of Contents

|                      |   |
|----------------------|---|
| Hand Held Tool.....  | 3 |
| Hydraulic Tool ..... | 4 |
| Soldering Tool ..... | 5 |

## Hand Held Tool

### BAND DRIVER AND BANDIX



BAND DRIVER



BANDIX (Big & Small Size)

### RATCHET CRIMPING TOOL



HS-8 CRIMPING TOOL  
FOR NON-INSULATED TERMINAL

| MM <sup>2</sup> | AWG  | WEIGHT(Kg) |
|-----------------|------|------------|
| 1.25-8          | 16-8 | 0.6        |



HS-16 CRIMPING TOOL  
FOR NON-INSULATED TERMINAL

| MM <sup>2</sup> | AWG  | WEIGHT(Kg) |
|-----------------|------|------------|
| 5.5-16          | 10-6 | 0.6        |



HS-16 CRIMPING TOOL  
FOR NON-INSULATED TERMINAL

| MM <sup>2</sup> | AWG  | WEIGHT(Kg) |
|-----------------|------|------------|
| 1.25-16         | 16-6 | 0.6        |



HS-38 CRIMPING TOOL  
FOR NON-INSULATED TERMINAL

| MM <sup>2</sup> | AWG  | WEIGHT(Kg) |
|-----------------|------|------------|
| 5.5-38          | 10-2 | 0.92       |



LY-03C RATCHET CRIMPING TOOL  
FOR INSULATED TERMINAL AND CONNECTOR

| AWG   | WEIGHT(Kg) |
|-------|------------|
| 20-10 | 0.6        |
| 20-16 | 0.6        |
| 14    | 0.6        |
| 12-10 | 0.6        |



HS-04WF RATCHET CRIMPING TOOL  
FOR FERRULES TERMINAL

| AWG   | WEIGHT(Kg) |
|-------|------------|
| 16-10 | 0.35       |



HX-50,120,150 CRIMPING TOOL  
FOR CABLE LUG

| MM <sup>2</sup> |
|-----------------|
| 6-50            |
| 10-120          |
| 25-150          |



HS-313 CRIMPING TOOL  
FOR CABLE LUG

| MM <sup>2</sup> |
|-----------------|
| 1.25-6          |

## Hydraulic Tool



REC-415F BATTERY OPERATED  
HYDRAULIC TOOL

| SIZE (mm)      | SPECIFICATION  | WEIGHT(Kg) | ACCESSORIES  |
|----------------|--|------------|--|
| 330 X 250 X 70 | RAM STROKE: 15mm<br>MOTOR:14.4 VDC<br>CAPACITY: 60cc | 3.2        | T-20, T-26, T-44<br>T-60, T-76, T-98<br>T-122 DIES<br>(1) BP-70E BATTERY<br>CH-25R/25EMC CHARGER |



EP430 HAND OPERATED  
HYDRAULIC TOOL

| SIZE (mm)      | WEIGHT(Kg) | SPECIFICATION                       |
|----------------|------------|-------------------------------------|
| 330 X 250 X 70 | 6          | RAM STROKE: 25mm<br>CAPACITY: 124cc |

## HYDRAULIC HOLE PUNCHER



SH-10 HYDRAULIC PUNCH

| SIZE (mm) | SPECIFICATION   | WEIGHT(Kg) | ACCESSORIES   |
|-----------|---|------------|---|
| 63 X 125  | RAM STROKE: 25mm<br>HOLE DIA UP TO 104mm<br>OUTER FACE 8.9 METRIC | 1.9        | MILLI SIZE PUNCH SETS ARE<br>AVAILABLE ON REQUEST.<br>M50,16,25,30,35,40,45,50,55,57<br>67,70,80,82,87,95,100,108,110 |



SH-5PD HAND HYDRAULIC PUNCH

| SIZE (mm) | WEIGHT(Kg) | SPECIFICATION                            |
|-----------|------------|--|
| 420       | 3.2        | OUTER FACE: 7.5 METRIC<br>CAPACITY: 66cc |

## Soldering Tool



Soldering Iron

### Non-temperature Controlled

|      |     |      |      |     |      |
|------|-----|------|------|-----|------|
| 110V | 15W | 100W | 220V | 15W | 80W  |
|      | 30W | 150W |      | 20W | 100W |
|      | 40W | 200W |      | 25W | 150W |
|      | 60W | 300W |      | 30W | 200W |
|      | 80W | 500W |      | 40W | 300W |
|      |     |      |      | 60W | 500W |



Rechargeable Irons

### About the cordless rechargeable series

- Tip Temperature reaches 900°F in less than 10 seconds
- Ceramic tip design eliminates damaging electrical leaks
- Lightweight, balanced design
- Equivalent power of 25W
- Convenient lighted iron illuminates work area

### Applications

- Automotive and truck repairs
- Aviation service and repairs
- Electrical Components
- Environmental splicing
- Infield repairs
- Jewelry repair
- Solder circuit boards



Soldering Gun

### Products Features :

- All purpose gun, 120V or 240V
- Dual -heat gun produces 140 or 100W with pistol grip design
- Temperature Range 1020°F / 900°F
- Cord Length 6ft
- Fingertip trigger selects high (1st trigger position)
- Or low output (2nd trigger position), ready to use in 6 seconds
- High efficiency, tin-plated copper tip
- Light illuminates work
- UL and cUL listed



Solder Sucker

To use, depress the end to engage the vacuum.  
Then heat up the to-be-desoldered joint until it is liquid.  
With your other hand hold the plastic tip as close as possible to the joint  
and depress the button to suck up all the liquid solder.  
If necessary, clean up the remaining solder with wick.